


FEATURES:


- Input: AC 100-240V~ 50/60Hz
- AC INLET: C8 or C6 or C14
- Power: 180-200W series
- Ovp, ocp, scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 179*85*40mm
- Application: Consumer electronics, Telecom and office equipment



IEC 60320 C6



IEC 60320 C8



IEC 60320 C14

SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55035 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

180W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-1201500-S20	100-240VAC	180W	12V	15.0A	C8, C6, C14
SW-1501200-S20	100-240VAC	180W	15V	12.0A	C8, C6, C14
SW-2400750-S20	100-240VAC	180W	24V	7.5A	C8, C6, C14
SW-3600500-S20	100-240VAC	180W	36V	5.0A	C8, C6, C14
SW-4800375-S20	100-240VAC	180W	48V	3.75A	C8, C6, C14

200W DESKTOP ADAPTERS SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	INLET TYPE
SW-1501200-S20	100-240VAC	180W	15V	12.0A	C8, C6, C14
SW-2001000-S20	100-240VAC	200W	20V	10.0A	C8, C6, C14
SW-2400830-S12	100-240VAC	200W	24V	8.3A	C8, C6, C14
SW-3600500-S12	100-240VAC	200W	36V	5.0A	C8, C6, C14
SW-4800416-S12	100-240VAC	200W	48V	4.16A	C8, C6, C14

Mechanical Diagram:

